



County of Lake, Ohio

OFFICE OF THE
COUNTY ENGINEER

March 14, 2013

FOR COUNTY PROJECT NO. 13-003-04
2014 Tandem Truck Cab & Chassis
Lake County Engineer Garage

LAKE COUNTY ENGINEER QUOTATION

ADDENDUM NO. 1

The following is Addendum No. 1 to the bid documents for: 2014 Tandem Truck Cab & Chassis.

1. The entire Specifications Portion of the bid document (11 pages) is to be replaced with the REVISED Specifications attached.

Changes were made in the following sections:

- **Page 6 – #9. – Cab/Hood:**
 - d. – 1. Revised verbage
 - d. – 2. Additional item added
- **Page 8 – #10. – Frame:**
 - b. – 10. Corrected statement
- **Page 10 - #17. – Paint:**
 - a. Corrected color

This addendum shall be attached to the proposal and become part of the bidding document to verify receipt of same.

www.lakecountyohio.org/engineer
550 Blackbrook Road ~ Painesville, OH 44077
Phone: 440/350.2770 ~ Fax: 440/352.8133

2014 TANDEM TRUCK CAB & CHASSIS SPECIFICATIONS – REVISED

The purpose of these specifications is to identify the equipment and components necessary to complete one (1) tandem truck and chassis unit for the Lake County Engineer.

The award will be made to a recognized body truck manufacturer. The truck company will be responsible for supplying and mounting of all identified items. Any parts not specifically mentioned which are necessary to provide a fully functional truck cab and chassis shall be furnished by the successful bidder. Materials and components supplied by the bidder shall be the latest current model incorporating each manufacturer's latest engineering change. Descriptive literature, complete specifications and all other necessary data to evaluate the proposed equipment shall be included with the bid. Failure to do so will invalidate the bid.

Any and all variations from the specifications must be noted on the specification sheet under the column labeled "COMPLY/ EXCEPTION". If there is an exception noted, bidder shall supply literature and detailed specifications of what will be supplied in lieu of what has been specified.

Each manufacturer/contractor shall guarantee against defective workmanship and material for electrical, engine, and transmission systems for a period of at least 24 months unless a longer warranty period is generally in effect by the respective manufacturer/contractor. Components, parts or material found to be defective shall be replaced by the bidder or manufacturer at no cost to the County. All additional and available optional warranties shall be included with bidder's proposal at the time of bid opening.

Upon delivery of the completed unit the bidder will supply a complete set of operating, repair and parts manuals on an "Interactive" CD, for each respective system and component supplied in this bid letting. A sample of Bidders "Interactive" CD shall be supplied with each bidder's proposal.

(SEE FOLLOWING PAGES FOR TRUCK GUIDELINES AND SPECIFICATIONS)

**2014 TANDEM TRUCK CAB & CHASSIS – REVISED 3/14/13
Lake County Engineer Garage – Project No. 13-003-04**

TRUCK GUIDELINES AND SPECIFICATIONS		Comply / Exception
1.	Engine	
	<ul style="list-style-type: none"> a. 6-cylinder diesel <ul style="list-style-type: none"> 1. 300 HP @ 2100 gov. RPM- Min. 325 HP Peak @ 1500 – 1900 RPM 2. Maximum Torque: 1200 lb/ft @ 1100 - 1300 RPM, 60% Torque Rise 3. 659 cu. In. displacement (minimum) 4. Lube oil system, Two full flow ESI spin on oil filters 5. Extended service interval 6. Centrifugal oil filter - Inverted 7. Flywheel housing – Die Cast Aluminum 8. Hand Primer Pump 9. Silicone hoses and tubing on engine 10. Air compressor, 18.7 cfm. Minimum Rating 11. Crankshaft PTO – 1350 Series 12. Oil Pan – single piece E-Coated steel 13. Engine brake 14. Engine shall be positioned low in the chassis, providing a lower center of gravity 15. Electrical pre-heater 16. Racor 1000 FH, 12V Electrical Heater w/integral Fuel/Water Separator 17. Fan drive, Borg Warner (Kysor) Cool Logic Fan Drive (HDMS) Electronically Controlled Variable 18. Diesel Particulate Filter mounted RH side under cab 19. Fuel-Water Separator – with manual drain valve (Integral w/primary fuel filter) 	
2.	Starting System	
	<ul style="list-style-type: none"> a. Starter, 12-volt – Gear Reduction b. Electronic starter interlock c. Batteries, (3) 12 volt, 1950 total CCA 	

TRUCK GUIDELINES AND SPECIFICATIONS		Comply / Exception
	d. Alternator, 12V 160A, Delco (24 SI)	
3.	Air Intake System:	
	<ul style="list-style-type: none"> a. Air Cleaner – Single element dry type with both hood side Intake, inside/outside with in cab control b. Air restriction monitor to be part of enhanced dash board electronic maintenance monitoring c. Diesel Particulate Filter Vertical – R.H. under cab d. Radiator mounted bug screen 	
4.	Exhaust/Emissions	
	<ul style="list-style-type: none"> a. Exhaust after treatment diesel particulate filter, ceramic catalyzed <ul style="list-style-type: none"> 1. DPF, Cleartech HHS DPF RH Side under Cab W/SCR Frame MTD RH Side 2. The engine shall be compliant and certified to meet the 2010 Federal EPA Emissions Standards <u>without using Federal EPA Credits</u>. The engine shall meet Federal Emissions Standards <u>using selective catalyst reduction</u>. 3. Exhaust after-treatment system-Exhaust after-treatment system diesel particulate filter ceramic passive regeneration 4. DPF Smart Switch, No inhibit DPF Regeneration Switch 5. Exhaust, Single stanchion or single cab MTD, single (R/S) vertical exhaust cab mounted, lower venturi diffuser, turned end. 6. Single, Bright finish heat shield and stack 7. Exhaust shall provide clear CA with no interference for body installation 	
5.	Cooling System – Shutterless Type	
	<ul style="list-style-type: none"> a. Radiator 900 sq. in. frontal area – minimum – aluminum core <ul style="list-style-type: none"> 1. Anti-freeze to –34 degree Fahrenheit 2. Fan drive, Borg Warner Cool Logic Electronically Controlled 3. Hoses, heater and radiator, silicone 	

TRUCK GUIDELINES AND SPECIFICATIONS		Comply / Exception
	<ul style="list-style-type: none"> 4. Poly V Fan Belt w/Automatic Tensioner 5. Coolant Conditioner 	
GENERAL INSTALLATION GUIDELINES AND SPECIFICATIONS		Comply / Exception
6.	Transmission:	
	<ul style="list-style-type: none"> a. Allison 3000-RDS-6 (3.49/0.65) Rugged Duty Series Gen 4 6-speed Automatic Transmission <ul style="list-style-type: none"> 1. Includes Transmission Oil Cooler, External oil Cooler, Internal Filter and Oil level sensor 2. Driveline - Interaxle Spicer SPL 170XL "Extended Lube Series" 3. Allison Transmission Shift to neutral when Parking Brake Engaged. 4. Transynd Synthetic Lube for Allison Transmission. 5. Bidder shall furnish data for all forward and reverse gears showing operating range. 	
7.	Cab: Interior	
	<ul style="list-style-type: none"> a. Custom trim level – Above base level <ul style="list-style-type: none"> 1. Coat hook 2. Power Outlet 3. Dispatch box 4. Overhead console including location for radio and in dash storage 5. Instrument cluster driver display with enhanced 4.5" diagonal graphic LCD display with 4 button stack control which includes routine maintenance monitoring of chassis 6. Visibility doors with passenger side peep window 7. Air conditioner, Heater & defroster 8. (4) Dome lights with self contained switch 9. Brake and accelerator pedal to be of "suspended" type 10. Adjustable Tilt steering column 	

TRUCK GUIDELINES AND SPECIFICATIONS	Comply / Exception
<p>b. Seats:</p> <ol style="list-style-type: none"> 1. Driver's Air-National 2000 (Hi-Back) Single Chamber Air Lumbar, 2 position front 2. Arm rest, inboard mounted arm rest – driver's seat only 3. Rider's seat non-suspension. 4. Diagonal grab handle on inside drivers door 5. Cloth / Vinyl seat trim 6. Seat Belts – Driver's and Rider's - Lap & Shoulder with seat retractor <p>c. Sun Visor, LH & RH</p> <ol style="list-style-type: none"> a. Floor mats, polyurethane with closed cell vinyl nitrile backing b. Form fitting noise control firewall mats shall be placed over the in-cab dog house c. AM/FM premium stereo CD with Weather band, MP3, WMA, Bluetooth 	
<p>8. Operational:</p>	
<ol style="list-style-type: none"> a. Wrap-around instrument panel, wood grain finish and driver & passenger side cup holders (HVAC Mtd). All dash controls are to be placed within easy reach of the driver. <ol style="list-style-type: none"> 1. Air pressure gauge 2. Voltmeter 3. Fuel level gauge 4. Engine oil pressure gauge 5. Engine coolant temperature gauge 6. Low air pressure indicator (light & buzzer) 7. Speedometer/Trip odometer – electronic 8. Tachometer/hour meter – electronic 9. "Parking Brake On" indicator 10. High beam indicator b. Provide (6) misc switches, (2) 15A IGN, (1) 20A IGN, (1) 10A IGN, (1) 15A BAT, and (1) 20A BAT c. 5 lb fire extinguisher between LH seat base and door with valve aimed rearward 	

TRUCK GUIDELINES AND SPECIFICATIONS	Comply / Exception
<ul style="list-style-type: none"> d. Emergency triangle kit parallel to inside surface of rider's seat base e. Key type starting f. Engine shut-off, key type control g. Courtesy light switch (head & clearance) – in cab lighting shall consist of 4 overhead lamps h. Directional signal switch, manual canceling i. Electric window lift – RH & LH w/power door locks j. Two extra dash mounted illuminated toggle switches k. Power outlets – Two (2) additional 12 Volt l. Dash control power supply for local installation of plow lamps w/lead at grille m. One-Piece Heated Windshield 	
<p>9. Cab/Hood: (exterior features)</p>	
<ul style="list-style-type: none"> a. Welded steel shell, galvanized <ul style="list-style-type: none"> 1. Rust preventative procedures b. Vents, screened <ul style="list-style-type: none"> 1. Fresh Air Inlet for heater c. Cab step, RH – Two Step frame mounted aluminum d. Safety glass windows <ul style="list-style-type: none"> 1. 1-Piece Tinted, heated windshield 2. 1-Piece Tinted side and rear glass 3. Windshield wipers – two, fixed arm & blade 4. Wiper motor (electric), (1) two speed, intermittent 5. Windshield washers, electric, wiper mounted with 5 qt. Reservoir e. Mirrors, Heated West Coast, Bright Finish <ul style="list-style-type: none"> 1. RH & LH with stainless steel arms & brackets, Motorized and Illuminated 2. Convex mirrors integral with Westcoast mirrors 3. Driver's view looking out the passenger side rear view West Coast mirror shall not be blocked by the RH exhaust 	

TRUCK GUIDELINES AND SPECIFICATIONS	Comply / Exception
<ul style="list-style-type: none"> f. Headlights, halogen flush mounted with integral turn signal <ul style="list-style-type: none"> 1. Identification & clearance lamps (5) 2. Side markers – lamps & reflectors 3. Front turn signals 4. 4-way flashers 5. Daytime running lights g. Horns electric (single tone) <ul style="list-style-type: none"> 1. Air, single trumpet with snow shield h. Doors – galvanized steel with peep window RH <ul style="list-style-type: none"> 1. Aluminum grab handles, RH & LH behind door 2. Diagonal Grab Handle on inside of driver's door i. Cab mounting: trunnion front, air suspended rear j. Hood and fenders, one piece molded fiberglass - camoplast <ul style="list-style-type: none"> 1. Tilts forward 75 degrees minimum 2. Stationary grill 3. Replaceable fender extensions 4. Hood insulation 	
<p>10. Frame:</p>	
<ul style="list-style-type: none"> a. Wheelbase: 207" <ul style="list-style-type: none"> 1. Load platform: 194" 2. Usable cab to axle: 120", <u>Clear Frame</u> 3. Axle to end of frame: 74" b. Frame rails – steel <ul style="list-style-type: none"> 1. Cross section, 11.811" x 3.54" x .37" 2. Section modulus – 29.80 cu.in. (minimum), double channel frame rail 3. RBM 3,580,000 in. lb. Per rail (minimum), 120,000 PSI yield strength 4. Frame Reinforcement – Inside channel – 5mm full length of main rail, extended to front bumper – parent material, for full IC Reinforcement. 5. Cross members: Back of cab to rear axle; Heavy duty back to back channels, extended behind rear axle; Single channel type 	

TRUCK GUIDELINES AND SPECIFICATIONS		Comply / Exception
	<ul style="list-style-type: none"> 6. Bumper: Steel, swept back channel 7. Towing hooks – Front 8. The space between the frame rails needs to be 8.5 inches wider at the front of the frame at engine compartment than it is at the cab firewall. 9. Tectyle Coating between frame rails for water tight seal. 10. Front frame extension <u>20-inches</u> for snow plow mount (Continued Parent Rail) with tilt, without inspection hatches. 	
11.	Fuel Tanks:	
	<ul style="list-style-type: none"> a. Aluminum 22" Diameter Step Type <ul style="list-style-type: none"> 1. Capacity/location: 116 gallon LH b. Standard Finish Steps and Bright Finish Straps 	
12.	Front Axle:	
	<ul style="list-style-type: none"> a. 20,000 lb. Capacity – Forged I-Beam construction b. Brakes, "S" Cam (16.5 x 6") Cast Spider <ul style="list-style-type: none"> 1. Bendix ES165-06D 2. Automatic slack adjusters 3. Dust shields 4. Unitized wheel hubs – requires no maintenance – permanently sealed with grease c. Sealed tapered kingpins and bearings d. Suspension, Multi-Leaf Spring Heavy Duty <ul style="list-style-type: none"> 1. 20,000 lb, ground load rating 2. 32.5" spring centers 3. Shock Absorbers e. Steering, Sheppard SD110 + HD94 power <ul style="list-style-type: none"> 1. Wheel equipment, steel disc – 22.5 x 9.0 Accuride 2. Hub Pilot – 10 Hole 3. Power coating – front hubs, ferrous 	
13.	Rear Axle:	
	<ul style="list-style-type: none"> a. 40,000 lb. Capacity axle 	

TRUCK GUIDELINES AND SPECIFICATIONS		Comply / Exception
	<ol style="list-style-type: none"> 1. Carrier – malleable-single reduction 2. Ratio: to obtain 64 mph @ gov. speed : 6.14 Ratio <p>b. 46,000 lb capacity – Air Ride Suspension – 52" axle spacing</p> <ol style="list-style-type: none"> 1. Height Control Kit 2. Shock Absorbers – (4) outboard-mounted on forward and rear axles, each side. 3. Oil Seals – Chicago Rawhide (Scotseal) 4. Transverse Torque Rod (Rear Axle Only) 5. Power Divider Lockout with Warning Light and Buzzer. <p>c. Brakes -Bendix ES165-07D, 16.5 x 7" – cast outboard mounted</p> <ol style="list-style-type: none"> 1. Bendix Anti-Lock Brake System with Traction Control 2. Automatic slack adjusters – Gunite 2000 3. Auxiliary spring brake chambers – Tamper resistant – MGM Model TR-T 4. 30/30 double diaphragm type – Must be top of axle mounted. 5. Mechanical spring release 6. Dust Shields <p>d. Wheel equipment, steel disc – 22.5 x 8.25</p> <ol style="list-style-type: none"> 1. (10 hole hub-piloted)(two hand-hole) 2. Rim – 8.25" x 22.5" 3. Powder Coated 	
14.	Tires:	
	<ol style="list-style-type: none"> a. Front (singles), Size: 315/80R22.5 – 20 Ply, Tread: M-860, Vendor: Bridgestone b. Rear (duals), Size: 11R22.5 – 14 ply, Tread: GL320 (Traction) Vendor: Bridgestone 	
15.	Brakes:	
	<ol style="list-style-type: none"> a. Anti-Lock System, Bendix with Traction Control b. Air dryer – Meritor/Wabco Heated Air Dryer 1200P w/coalescing oil filter c. Air Reservoir – Two, aluminum, standard finish 	

TRUCK GUIDELINES AND SPECIFICATIONS		Comply / Exception
	<ul style="list-style-type: none"> d. Trailer Air Brake Connections, end of Frame e. Trailer Electrical Receptacle – Single 7 Pins Std, SAE Type, End of Frame 	
16.	Electrical:	
	<ul style="list-style-type: none"> a. Negative ground b. 12-volt electrical circuits & bulbs c. Circuit protection, all circuits breaker protected d. Battery Box Covers – Polished aluminum e. Battery shock pads f. Electrical connections, waterproof, sprayed with protective coating g. Cab floor pass thru hole / rubber boot h. Rear lighting, (2) combination stop, tail directional and back up lights i. Truck to meet 2014 On-Board Diagnostic Requirements 	
17.	Paint:	
	<ul style="list-style-type: none"> a. Cab, hood & fenders, Color: Omaha Orange – high gloss PPG-60361 or equal with urethane clear coat b. Chassis running gear, Color: Black – Urethane. 	
18.	Miscellaneous:	
	<ul style="list-style-type: none"> a. Dealer to state warranty and any recommended optional extended warranties and cost of each on bid price sheet b. Literature & Factory Computer Printouts c. Dealer to furnish all available printed literature on chassis & individual drive train components with bid d. Dealer to furnish computer analysis with bid, Indicating performance, operating range – MPH e. Parts and Service, must be available at bidders facility within a radius of 35 miles <p><i>**Subject to approval of Lake County Engineer**</i></p>	

DETAILED EXCEPTION SHEET

List here any and all exceptions to specifications upon which your bid is based. If there are no exceptions listed here, your bid will be considered to be in complete accordance with specifications.