Table of Contents

Section	Page		
1. Pipe and Fittings – Sec. 2.01 Rules and Regs.			
A. Pipe Couplings	3		
B. Pipe Repair Clamps	3		
C. Fittings – Full Body	3, 4		
D. Manufactured Restraint Joint Pipe	4		
E. Mechanical Joint Pipe	4		
F. Mechanical Joint Restraint	4		
G. Restrained Flange Adapter	5		
H. Ductile Iron Pipe	5		
I. PVCO C909 Pipe	5		
2. Steel Encasement Pipe – Sec. 2.05 Rules and Regs.			
A. Casing Chocks	5		
3. Gate Valves – Sec. 2.06 Rules and Regs.			
A. Resilient Wedge and OS&Y	5, 6		
4. Tapping Sleeves and Valves – Sec. 2.07 Rules and Regs.			
A. Tapping Sleeves	6		
5. Valve Box – Sec. 2.09 Rules and Regs.	7		
6. Meter Vaults – Sec. 2.10 Rules and Regs.			
A. Access Hatch Doors - Non Traffic Bearing	7		
B. Castings and Covers – Traffic Bearing	7		
7. Fire Hydrants – Sec. 2.12 Rules and Regs.			
A. Hydrants	8		
B. Hydrant Anchor (swivel) Tee	8		
C. Concentric Reducer	8		

Rev: 3/31/2021 1 | Page

Manufacturer Model Number Size **Comments** 8. <u>Service Connections – Sec. 2.15 Rules and Regs.</u> A. Bronze Service Saddles 8 B. Corporation Stops 8 C. Curb Box 9 D. Curb Stops 9 E. Union Fittings/Adapters 9 9. Meters and Settings – Sec. 2.25 Rules and Regs. A. Combination Meter 10 10 B. Domestic Meter C. Angle Yoke Ells 10 D. Angle Yoke Valves 10, 11 E. Yoke Expansion Connector 11 11 F. Yoke G. Frame and Cover 11 H. Meter Lid Cover 11 I. PVC Meter Vault 12

1. Pipe and Fittings – Sec. 2.01 Rules & Regs.

Rev: 3/31/2021 **2 |** P a g e

Manufacturer Model Number

<u>Size</u> <u>Comments</u>

A: Pipe Couplings –	**Minimum 304 Stainless Steel Bolt and Nut Required**		
Dresser	-253		
4"-16" Nom. Size			
Hymax	- 2000 Series		
4"-24" Nom. Size	Long Sleeve Available		
Romac	- 501, XR501		
2"-24" 501, 4"-12" XR501			
Romac	- RC-501, EC-501		
4"x3", 6", 8"x6", 10", 4"	′x16″		
Smith Blair	- 441,442, 461, 462,		
2"-16" 441, 4"-12" 461			
B. Pipe Repair Clamps			
Smith Blair	- 256, 257		
2"-14" Nom. Size	3/4" to 2" Threaded Outlets Available		
<u>C. Fittings C110 – <i>C153</i></u>	**Minimum 304 Stainless Steel Bolt and Nut Required**		
Clow/McWayne	- Cement lined		
3" to 36"			
U.S. Pipe	- Cement lined		
3" to 48"			
Star	- Cement lined		
2" to 54"			
Sigma	- Cement lined		
3" to 24"			
Tyler/Union/Ufco	- Cement lined		
2" to 48"			

Rev: 3/31/2021 **3 |** P a g e

<u>Manufacturer</u> <u>Model Number</u>

<u>Size</u> <u>Comments</u>

D. Manufactured Restraint Joint Pipe (Boltless Restraint) -

Class 53 Unless Otherwise Specified

Clow/McWayne - Super Lock boltless

6" to 36"

American - Flex Ring Pipe boltless

4" to 48"

U.S. Pipe -TR Flex boltless

4" to 36"

E. Mechanical Joint Pipe - **Minimum Class 53 Unless Otherwise Specified**

Clow/McWayne

3" to 24" / 30" to 36"

American

4" to 48"

US Pipe

4" to 48"

F. Mechanical Joint Restraints - **Minimum 304 Stainless Steel Bolt and Nut Required**

Ford "Domestic Made Only" - Uni-Flange – 1400 series, 1500 Style for C909

3" to 36"

Ebba Iron Inc. -1100 series

3" to 48"

Sigma One-Lok - SLDE

3"- 36" - 30", 36" require SIGMASEAL improved gasket

- SLCEH Harness for C909 Restraint

G. Restrained Flange Adapter

Ebba Iron Inc. -2100 Series

Rev: 3/31/2021 4 | Page

<u>Manufacturer</u> <u>Model Number</u>

<u>Size</u> <u>Comments</u>

3" to 48"

H. Ductile Iron Pipe - **Minimum Class 53 Unless Otherwise Specified**

US Pipe - Tyton

4" to 64"

American - Fastite

4" to 64"

Clow/McWayne - Tyton/Fastite

3" to 36"

I. PVCO C909 Pipe - **Pressure Rating 235 Minimum**

JM Eagle - Ultra Blue D.I.P.S Only

6" to 16"

Bionax - D.I.P.S Only

4"- 30"

2. Steel Encasement Pipe – Sec. 2.05 Rules and Regs.

A. Casing Chocks - (Stainless Steel)

Power Seal Pipeline Products – 4810

As Needed @ 10' Intervals Max.

Cascade Waterworld Mfg.

As Needed @ 10' Intervals Max.

Advance Products and Sys. I – SS1

As Needed @ 10' Intervals Max.

3. Gate Valves - Sec. 2.06 Rules and Regs.

Rev: 3/31/2021 **5** | P a g e

<u>Manufacturer</u> <u>Model Number</u>

<u>Size</u> <u>Comments</u>

A. Resilient Wedge and OS&Y (MJ and Flanged Ends) - **Minimum 304 Stainless Steel Bolt

and Nut Required**

Mueller - 2361, 2362

2" to 12" / 14" to 36"

Kennedy

2" to 16"

American Flow Control - 2500

2" to 16"

Clow

2" to 16"

4. Tapping Sleeves and Valves – Section 2.07 Rules and Regs.

A. Tapping Sleeves

Stainless Steel Outlets ONLY - **15" Minimum Width**

JCM - 439

4" to 24"

Romac Industries - SSTIII

4" to 30"

Smith Blair - 663, 665

4" to 24"

Mueller - 304MJ

4" to 24"

Power Seal - 3480MJ Up to 16"

4" to 24" - 3490MJ Greater than 16"

Rev: 3/31/2021 6 | Page

Manufacturer Model Number

<u>Size</u> <u>Comments</u>

5. Valve Box - "Water" on Lid- 3 Piece Screw Type - Sec. 2.09 Rules and Regs.

Heavy Duty Top Section ONLYSlotted lid ONLY**

Bingham Taylor

5.25"	Extensions available
Tyler	- 6860 Series
5.25"	Extensions available
Star	- VB0006 Series
5.25"	Extensions available
Sigma	-VB630
5.25"	Extensions available

Snake Pit For tracer box PVCO pipe C909 + HDPE

6. Meter Vaults – Section 2.10 in Rules and Regs.

A. Access Hatch Doors for Non Traffic Bearing Applications

Bilco

B. Castings and Covers for Traffic Bearing Applications

East Jordan Iron Works - 1710

Heavy Duty

Neenah - Model R-1782

Heavy Duty

Rev: 3/31/2021 **7** | Page

<u>Manufacturer</u> <u>Model Number</u>

<u>Size</u> <u>Comments</u>

7. Fire Hydrants – Section 2.12 in Rules and Regs.

A. Hydrants – Three Way Type -**All above and below ground bolts and nuts shall be 304 or 316 stainless steel. – All lower stems shall be 410 stainless steel.**

Mueller – Super Centurion 250 - A423

5.25" MVO

B. Hydrant Anchor (Swivel) Tees and 90's

Clow, Sigma, Star, Tyler Union, US Pipe

C. Concentric Reducer

Clow, Sigma, Star, Tyler Union, US Pipe

8. Service Connections – Section 2.15 Rules and Regs.

A. Bronze Service Saddles

Mueller - BR2B

4" to 16" Nom. Size Double Strap, ¾" to 2" Outlet

Smith Blair - 325

4" to 12" Nom. Size Double Strap, ¾" to 2" Outlet

Smith Blair - 372

4" to 16" Nom. Size Double bolt SS for C909

Use spring washer for HDPE 3/4" to 2" Outlet

B. Corporation Stops - **No lead/Low lead ONLY**

AY McDonald - 4701 or 4701-B - up to and including 1"

1" Min. New Construction - 4701-B – 1 ½" and 2"

Mueller - H15000 - up to and including 1"

Rev: 3/31/2021 **8** | Page

<u>Manufacturer</u>	Model Number		
<u>Size</u>	Comments		
1" Min. New Construction	- B25000 - 1 ½" and 2"		
Ford Meter Box Co.	- F600 - up to and including 1"		
1" Min. New Construction	- FB600 - 1 ½" and 2"		
C. Curb Box			
McWayne Bibby	-V005-V011		
2.5" Diameter	Screw Type		
Bingham and Taylor	- P-94-E		
2.5" Diameter	Screw Type		
Sigma	- VB794E		
2.5" Diameter			
D. Curb Stops – ¼ Turn Only - **No lead/Lo	ow lead ONLY**		
AY McDonald	- 76100		
1" Min. New Construction			
Mueller	- B-25204		
1" Min. New Construction			
Ford Meter Box Co.	- B-22 Series		
1" Min. New Construction			
E. Union Fittings / Adapters - **No lead/Low lead ONLY**			
Mueller	- H-15400		
1" Min. New Construction	- P-15403 – Customer Side ONLY		
AY McDonald	- 4758		
1" Min. New Construction			
Ford Meter Box Co.	- C22 Series		

Rev: 3/31/2021 9 | Page

 Manufacturer
 Model Number

 Size
 Comments

 1" Min. New Construction
 - C44 - Customer Side ONLY

9. Meters and Settings - Section 2.25 in Rules and Regs.

A. Combination Meter - Remote Read

Sensus - Omni F2

4" and Above

Octave - Ultrasonic

2" to 12"

B. Domestic Meter - Remote Read

Master Meter - Multi Jet

1" to 2"

Sensus - Omni C2 or T2

1 1/2" and 2"

C. Angle Yoke Ells - **No lead/Low lead ONLY**

Ford - L92 Series

¾" to 1"

Mueller - H-14202

¾" to 1"

AY McDonald - 4779Y

¾" to 1"

D. Angle Yoke Valve - **No lead/Low lead ONLY**

AY McDonald - 4602Y

3/4" to 1" - 4602BY

Ford - AV92 Series

Rev: 3/31/2021 **10** | P a g e

<u>Manufacturer</u>	Model Number		
Size	Comments		
¾" to 1"	- BA92 Series		
Mueller	- H14264		
¾" to 1"	- B24264		
E. Yoke Expansion Connector - **No lead/Low lead ONLY**			
AY McDonald	- 14-2 EHG, 14-4 EHG		
3/4" / 1"			
Mueller	- H-14234		
3/4" / 1"	3 piece with O-ring		
Ford	- EC-23, EC-4		
3/4" / 1"			
<u>F. Yoke</u>			
AY McDonald	-14-2 / 14-4		
3/4" / 1"			
Mueller	- H-5020 / H-5040		
34" / 1"			
Ford	- Y-502 / Y-504		
34" / 1"			
G. Frame and Cover			
East Jordan	- 2890		
,	Non Traffic Bearing		
H. Meter Lid Cover			
Ford	C-32-T, C3-T, C4-T		
18" to 24" Diameter			

Rev: 3/31/2021 **11 |** P a g e

Manufacturer Model Number

<u>Size</u> <u>Comments</u>

I. PVC Meter Vault 30" Depth

Carson / Sonoloc / ADS

18" through 30" Diameter PVC Meter Vault

Rev: 3/31/2021 12 | P a g e